



TF110R-TRS

Battery, LPG or petrol powered ride-on sweeper. Powerful dust control. Optional high-dump hopper. For cleaning net floor surfaces of up to 12,000m².



TF110R-TRS

A compelling combination of durability, outstanding sweeping results and dust control makes the TF110R-TRS the preferred choice for construction sites, building material manufacturers, distribution hubs and other demanding applications.

- Spring loaded side brushes retract behind the chassis on impact with objects such as racking or walls to protect from damage.
- Foam filled non-marking tyres give operators a smooth and more comfortable ride even on rough terrain whilst retaining the puncture resistant attributes of solid wheels.
- Up to 5 hours operation on a single charge.
- Clear control layout with individually operated functions minimise training requirements and resettable fuses protect motors from overload.
- Fast and easy no-tools access to main brooms, side brushes, filters and main components for reduced servicing downtime.

- Main broom and side broom height adjustment to compensate for wear.
- Powerful climbing ability means the TF110R-TRS can tackle inclines of up to 20%.
- Chain drive sweeping (rather than belt drive) reduces maintenance requirements and maximises power transmission.
- Each TF110R-TRS is delivered with a flashing beacon, back up alarm, horn, steering knob and non-marking tyres as standard, so that it's ready to roll in industrial applications.

The TF110R-TRS carries all the traits of a true Topfloor sweeper; powerful suction, straightforward operation and precision engineering.



“ When sweeping floors with a mix of large debris and a high volume of dust, the TF110R-TRS comes out trumps every time. ”

| TECHNICAL INFORMATION | TF110R-TRS | OPTIONAL EXTRAS |
|---|------------------------|--|
| Power Supply | Battery / LPG / Petrol | To personalise your Topfloor sweeper, a range of additional options are available: |
| Theoretical Productivity (m ² /hr) | 6,600 | <ul style="list-style-type: none"> • Side broom speed control to further reduce the airborne dust being whirled up. |
| Main Broom Width (mm) | 700 | <ul style="list-style-type: none"> • Hydraulic high-dump hopper reaches up to 130cm for easy emptying into an industrial bin. |
| Total Sweep Width (mm) | 1,100 | <ul style="list-style-type: none"> • Battery, LPG and petrol variants for fume free operation or constant running depending on your specific needs. |
| Hopper Capacity (ltr) | 90 | <ul style="list-style-type: none"> • Retractable 3rd and 4th side broom arms for sweeping small raised kerbs or increasing the overall sweep path. |
| Filter Area (m ²) | 4 | <ul style="list-style-type: none"> • On-board vacuum for cleaning between pallets, racking overhead and other surfaces in areas with no power supply. |
| Airflow Volume (m ³ /hr) | 900 | <ul style="list-style-type: none"> • Carpet kit for sweeping dust and debris from large carpeted areas quickly and effectively. |
| Max Speed (km/h) | 6 | For specific requirements, Topfloor machines can be bespoke built. To explore these options, simply contact us. |
| Turning Circle (m) | 1.2 | |
| Dimensions – L x W x H (mm) | 1,145 x 900 x 1,165 | |
| Weight – incl Battery (kg) | 331 / 230 / 260 | |

Product specification subject to change without prior notice.